



## ACCESSORIES : H-LF TYPE NEW PVC LAYFLAT HOSE

- HCP, H-LF Type, 2"~4" discharge hose that is made from impregnated PVC and reinforced synthetic yarn. High tensile, woven reinforcement provides great durability and strength in all working conditions.
- Features a working pressure of 4 kg/cm<sup>2</sup>, lightweight, easy to handle and flexible, long length with no limitation, convenient storage, oxidation resistant, and limited oil and chemical applications.
- Working temperature range: -10°C~65°C (14°F~149°F)



## PRODUCT FEATURES



**Epoxy Cable Base**

An epoxy resin seal cable base prevents moisture from entering the motor through the core wires.



**Double Mechanical Seals**

Superior abrasion resistant mechanical seal manufactured with silicon carbide to ensure the best seal effect.



**AUTOCUT**

Automatic On/Off motor protector to prevent motor burn out due to high temperature and excess amperage draw.



**High Efficiency Dry Motors**

All stator coils need to be treated with insulating varnish procedure to achieve the best insulation, efficiency and durability.



**GD/GDR** **50Hz** SERIES

SUBMERSIBLE PORTABLE  
DEWATERING / RESIDUAL PUMPS

Distributor:

Innovation • Professionalism • Service  
**HCP PUMP MANUFACTURER CO., LTD.**



We reserve the right to alter specifications of product at any time without giving prior notice.

[www.hcppump.com.tw](http://www.hcppump.com.tw)



GD-400/750

GD-F

GD-FV

## GD New Portable Dewatering Pumps

### FEATURE

- The GD models are designed for the construction industry because they are lightweight, portable, and durable. The motor frame and mechanical seal bracket are made of aluminum alloy – that provides extra water cooling, to the motor, when water flows through. Features an all new design with exchangeable discharges, that are available in vertical and horizontal orientation. They also provide extra adaptability and flexibility to various conditions of installations, such as: confined spaces, 8 inch narrow wells or shallow water.
- The model is equipped with: double mechanical seals (silicon carbide), epoxy resin cable, watertight body structure that meets IP68 requirements, an auto-cut motor protector, and a water-cooling motor.
- The impeller and the hydraulic components are made of a special rubber that is durable and capable of handling construction site dewatering.
- The models are available in the manual version and the automatic version – equipped with a built in floating switch to automatically switch the pump on and off.
- The impeller is made with an urethane rubber that provides extra wear-resistance on construction site dewatering.



#### Semi-open:


The semi-open vortex impeller is used in combination with a special made whirlpool volute casing that enhances the pump efficiency. The impeller is made with an urethane rubber that provides extra wear-resistance on construction site dewatering and is more durable than a cast iron impeller.

### APPLICATIONS

- Civil engineering, dewatering of tunneling and ground works, and for use in storm water sewers.
- Dewatering of fluids containing solids.
- Ease of mobility for use by contractors, installers and service industries.



### PERFORMANCE CURVES




### SPECIFICATIONS

Item	Description
Limits of Use	Liquid Temp. 0~40°C(32~104°F) Applications Wastewater · Sewage
Type	Frequency 50Hz Motor 2P(3000rpm) · Dry Motor Insulation Class B Protection IP68 Protector Auto-cut Bearing Ball type M.seal Double M.seals Impeller Semi-open
Material	Upper Cover ADC12 Motor Frame ADC12 Shaft End SUS410 M.seal CA/CE & SiC/SiC Casing Synthetic Rubber Impeller Urethane Rubber + SPCC Strainer SUS304 Cable VCT or H07RN-F or SJOW
Optional	Pumps can be customized to fit specifications

### PRODUCT NOMENCLATURE

GD Type — 400 Watt



### PERFORMANCE SPEC.

Model	Output HP (kW)	Discharge Inch (mm)	Phase Ø	Start Method	Head m	Capacity		Solid Passage mm	Weight kg	Dimension mm		
						m³/min	m³/h			∅	A	B
GD-400	0.5 (0.4)	2" (50)	1	Capacitor	8	0.1	6	7	10.5	230	185	305
GD-750	1 (0.75)	2" (50)	1	Capacitor	11	0.16	9.6	7	12.6	230	185	327

Note: Weight Not Included Cable & Outlet Set.

## PRODUCT FEATURES


- The model is equipped with a 50mm (2 inch) discharge that is available in vertical and horizontal. The exchangeable discharge prevents the layflat hose from folding because of the uneven ground.
- Two types of discharge connections are available: LOT threaded and LOH hose coupling. Thread type can be chosen between PF, PT, and NPT threads.
- The models are available in the automatic version, that has a floating switch (F) or a vertical type floating switch (FV), to automatically switch the pump on and off.




LOH 2" hose coupling discharge



LOT 2" threaded discharge



Application in shallow water - Horizontal orientation discharge and floating switch



Application in a pit and confined space - Vertical orientation discharge and vertical floating switch



### Motor :

Motor of lightweight and slim design that facilitates the installation of the pump in narrow and confined spaces.

### Wear Plate :

Wear Plate is specially made in a rubber that is durable and protects the mechanical seal bracket from wearing.

### Impeller :

The impeller is made of an urethane rubber that provides extra wear-resistance on construction site dewatering, and is more durable than a cast iron impeller.

### Casing :

Casing is made in a synthetic rubber that provides wearing resistance.

### Casing Cover :

Casing Cover is made in a combination of rubber and steel plate.

### Strainer :

Strainer is made in a stainless steel that is more resistant to rust than regular iron.





The GD Series of HCP Pump features a lightweight and slim design. The lightweight and small pump body makes this pump easy to carry to any corner of construction sites for dewatering. The slim design of the pump body also allows the pumps to be installed in drainage pipes or pits of construction sites, narrow wells, confined spaces, or shallow water. The Cooling Jacket design provides extra water cooling to the motor, when water flows through. The impeller and the hydraulic components are made of a special rubber that is durable and capable of handling construction site dewatering.



**GDR**  
Pumping down to lowest water level 1mm (0.39")

## GDR Portable Residual Pumps

GDR-400

### FEATURE

- A water cooling motor with rubber suction pads for residual removal as low as 1 mm (0.39").
- The best pump for removing water from flat surfaces because of its portability and light weight.
- Equipped with double seals (silicon carbide), epoxy resin cable, IP68, an auto-cut motor protector and rubberized hydraulic components that can withstand any tough applications.
- Standard discharge: Outlet Discharge 1" LOT 1-74 (Optional 2" LOT 2-74)




### SPECIFICATIONS

	Item	Description
Limits of Use	Liquid Temp.	0~40°C(32~104°F)
	Applications	Wastewater · Sewage
Type	Frequency	50Hz
	Motor	2P(3000rpm) · Dry Motor
	Insulation	Class B
	Protection	IP68
	Protector	Auto-cut
	Bearing	Ball type
	M.seal	Double M.seals
Material	Impeller	Semi-open
	Upper Cover	ADC12
	Motor Frame	ADC12
	Shaft End	SUS410
	M.seal	CA/CE & SIC/SIC
	Casing	Synthetic Rubber
	Impeller	Urethane Rubber + SPCC
	Cable	VCT or H07RN-F or SJOW
	Optional	GDR-400 2"

### APPLICATIONS



- Basement / Pool / Pond water removal.
- Residential, Commercial residue dewatering.

### PERFORMANCE CURVES



### PRODUCT NOMENCLATURE

GDR — 400  
Type Watt



### PERFORMANCE SPEC.

Note: Weight Not Included Cable & Outlet Set.

Model	Output HP(kW)	Discharge Inch(mm)	Phase Ø	Start Method	Head m	Capacity		Weight kg	Dimension mm		
						m³/min	m³/h		∅	A	B
GDR-400	0.5 (0.4)	1" (25)	1	Capacitor	8	0.07	4.2	10.5	209	205	305